

Model No. USV-110 Rackmount Utility Shelf w/Vented Base Panel Space: 1U or 1.75" [44] Overall Depth: 10.75" [273] Overall Width: 19.00" [483]

Made In The USA

Certified US Stee

RUGGED STEEL SHELF with VENTED BASE mounts to 19" E.I.A. compliant rack, providing support for non-rackmount equipment such as consumer electronics, power supplies, and chassis style components.

## FEATURES

Usable Width:

Load Capacity:

<u>CONSTRUCTION</u>: Single piece 16-gauge certified U.S. steel construction.

FINISH: Smooth black powder epoxy finish.

BASE: Fully vented base for passive ventilation.

17.31" [439]

50 lbs. [22.6 kg]

FRONT: Front flange (0.375") adds strength and helps keep equipment in place.

<u>REAR</u>: Slotted rear flange (0.56") provides tie-off points for cable management and notches to mount an optional power strip.

COMPLIANCE: E.I.A./T.I.A.

ORIGIN: Made in the U.S.A.

OPTIONS: (order separately)

- <u>ACS-1506-WW</u>: Compact AC power strip with six 15A NEMA outlets, spaced for power supplies, and attached cord.
- <u>ACS-1507</u>: Compact AC power strip with seven 15A NEMA outlets and detachable cord.

			l
11111			

Top view



Notches on the shelf's rear flange make it easy to mount a power strip (see options).

## A&E SPECIFICATIONS

The rackmount utility shelf shall be Lowell model USV-110 with overall dimensions of  $19"W \times 10.75"D \times 1U$ . It shall be 16-gauge certified U.S. steel construction with fully vented base and smooth black powder epoxy finish. It shall feature a front and rear flange. The rear flange shall have slots to provide tie-off points for cable management, and notches to mount an optional power strip. The shelf shall be made in the U.S.A. and have a load capacity of 50 lbs.







## USV SERIES SUMMARY

	Model No.	Panel Space	Overall Width	Useable Width	Overall Depth	Overall Height	Load Capacity	Material	Carton Pack
THIS SPEC	USV-110	1U	19.00 [483]	17.31 [440]	10.75 [273]	1.72 [44]	50 lbs. [23 kg]	16-ga. steel	1
	USV-214	2U	19.00 [483]	17.31 [440]	14.00 [356]	3.47 [88]	50 lbs. [23 kg]	16-ga. steel	1
	USV-314	3U	19.00 [483]	17.31 [440]	14.00 [356]	5.22 [133]	50 lbs. [23 kg]	16-ga. steel	1
	USV-414	4U	19.00 [483]	17.31 [440]	14.00 [356]	6.97 [177]	50 lbs. [23 kg]	16-ga. steel	1
	USV-218	2U	19.00 [483]	17.31 [440]	18.00 [457]	3.47 [88]	50 lbs. [23 kg]	16-ga. steel	1

Dimensions = inches [mm]; 1U = 1.75"

## TECHNICAL DRAWINGS

Dimensions are inches and [mm] unless stated otherwise.





