



Vandal-resistant intercom station with call switch features a heavy duty stainless steel wall plate and vandal-resistant screws with driver bit. The station is ideally suited for areas where vandalism may be a concern such as correctional facilities, public garages, lobbies, warehouses and similar areas.

FEATURES:

- **Wall Plate:**
 - Heavy duty 11-gauge stainless steel three-gang wall plate with brushed finish.
 - Shallow depth, can mount in a standard three-gang box
 - Internal offset baffles provide added protection from vandalism.
 - Includes vandal-resistant hardware for a high degree of security. (Torx head screws and driver bit)
- **Speaker:**
 - 45ohm, 6W, 98dB @1W, 300Hz-8kHz
 - Moisture resistant
 - Pigtail connections for easy field installation
 - For clear one-way or two-way communication
- **Transformer:**
 - 25V line 1W, 1/2W
 - Pigtail connections

• Call Switch:

- SPST (single pole, single throw)
- Rating: 1A 48VDC
- Function: Momentary (normally open)
- Screw terminal connections

A&E SPECIFICATIONS:

The vandal-resistant intercom station with call switch shall be Lowell VRIC-3G-4525, which shall feature a 45ohm speaker with 25V transformer and a push button call switch. The intercom station shall have three-gang wall plate, 11-gauge stainless steel with brushed finish. The unit shall feature offset baffles and include vandal-resistant screws and a driver bit.

OPTIONS: (order separately)

- **P1X-3 Box:** Surface-mount three-gang box, 20-gauge steel with knockouts, white finish. 4.625"H x 6.437"W x 2.5"D



VRIC Intercom Series Overview

Model No.	Description	Wall Plate	Speaker	Transformer	Height	Width	Depth
VRIC-2G-4525	Intercom station w/call switch	2-gang	45 ohm	25V	4.5"	4.47"	1.75"
VRIC-3G-4525	Intercom station w/call switch	3-gang	45 ohm	25V	4.5"	6.375"	1.75"

This spec

